

Model 27D

1100 Gallons Per Hour



| | 13.6v | 12.0v |
|--------------------------|-------|-------|
| GPH @ Open Flow | 1100 | 1050 |
| GPH @ 3.35' feet in lift | 860 | 720 |
| GPH @ 6.7' feet in lift | 600 | 480 |

| | 13.6v | 12.0v |
|----------------------|-------|-------|
| Amp Draw @ Open Flow | 5.0 | 3.3 |

FEATURES

- Fully Submersible
- Easy clean snap lock strainer
- Silent and vibrationless operation
- Anti-airlock protection
- Compact, efficient long life motor
- Ignition protected
- No burn-out when run dry
- Rust and Corrosion protection
- Used by leading boatbuilders worldwide
- marine grade blocked wiring

ANSWERS TO FREQUENTLY ASKED QUESTIONS

- Not self priming; will not pull water up to itself
- Discharge hose must run continually upwards
- Reductions in hose size will reduce output
- Increases in hose size will not increase output
- Reversed polarity runs pump at 20% capacity
- Increase wire gauge for each add'l 20 foot run
- Check valves are not recommended
- Install a vented loop for anti-siphoning
- Break in for 10 hours for maximum pumping
- Rule does not repair pumps - it is not cost efficient for the consumer
- Rule does not sell pump parts due to liability

CERTIFICATIONS

- NMMA Type Accepted Equipment # 704203
- IMCI Certified - ISO 8849
- CE Certified
- UPC Code 0-42237-08345-6

| Specification | |
|------------------------|----------------|
| Fuse Size | 6 amps |
| Discharge Opening | 1-1/8" |
| Discharge Finish | Barbed |
| Rule Hose | Model 80 or 83 |
| Rule Thru-Hull Fitting | Model 60 |
| Housing Material | ABS |
| Strainer Material | ABS |
| Impeller Material | Nylon |
| Shaft Material | Stainless |
| Seal Material | Nitril/Teflon |
| Temperature Limit | 200 F |
| Fluid Capabilities | Bilge Water |
| Typical Life | 1500 hours |
| Wire Length | 29" |
| Wire Gauge | 16 gauge |
| Weight | 10 oz |
| Height | 4-1/4" |
| Width | 2-3/8" |
| Depth | 2-3/8" |
| Strainer Replacement | M 275 |