Three Year Limited Warranty

Golight, Inc. warrants the Golight® against any deemed defects that are due to workmanship for parts or faulty materials, **except lamps**, for three years from the date of the original purchase. This warranty to the Golight® does not cover damage resulting from unreasonable use or misuse, unreasonable maintenance or loss, or labor costs.

Mounting the light upside down will void the warranty.

Warranty cards must be filled out and sent in within 30 days of purchase to Golight, Inc. • RT 3 Box 37B • Culbertson, NE 69024, for warranty protection. Register online at www.golight.com.

If the Golight® does fail to operate under warranted specifications, send the **light and remote controls** postage paid, plus \$9.95 for shipping and handling to: Golight, Inc. • Service Department • RT 3 Box 37B • Culbertson, NE 69024. No C.O.D.'s accepted. Only the above manufacturer is authorized to perform warranty repair or replace product.

Any consequential damages to person or property are excluded from this warranty. Some states do not allow the exclusion and limitation of incidental or consequential damages, therefore the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights and you may also have other rights.

GOLIGHT*

Golight, Inc.
RT 3 Box 37B • Culbertson, NE 69024
800.557.0098 • 308.278.3131
info@golight.com • www.golight.com

GOLIGHT[®]

MODEL 2020

Congratulations

You are now the owner of one of the finest remote control searchlights available today. Thank you for letting Golight® assist you in your lighting application needs. We're proud of our products and the technology that we've developed to ensure our customers the most durable, versatile and powerful searchlights in the lighting industry.

Please read these instructions before using your new Golight®.



nstruction Guide

The Golight® Model 2020 is designed to be permanently attached to a vehicle. The Searchlight with Directional Flexibility is controlled by a dash-mount remote, which gives the operator a full 370° horizontal rotation and a 135° vertical tilt with fingertip control. The Golight® provides superior light penetration with Cr5 PentaBeam™ technology.

The Golight® Includes:

- Golight® Searchlight
- Dash-Mount Remote Control (with guick connects.)
- 20' 6 Wire Cord with Positive & Negative 12 Volt Wire
- Permanent Mounting Gasket
- Screws and Caps

MOUNTING INSTRUCTIONS:

Determine location of dash-mount remote. Create an opening and insert dash-mount remote with correlating quick connect on 20' cord. Connect power wires to 12 v D.C.

The 12 Volt DC power wire should be joined to the leads on the 20' cable with appropriate automotive wire attachments. It is critical that polarity be observed. The (+) lead of the Golight® is marked with a red tag. The power should be fused at 15 Amps and be on an ignition switched circuit if possible.

Determine location for Golight®. (Extra 10' and 20' quick connect cords are available, if needed.) Create opening for Golight® cord. Place gasket on Golight® and attach correlating quick connect to Golight®. Use silicone sealant to fill opening. Set light in place and mount light base to surface with screws provided. Cover screws with the 4 white caps provided.

Attach Dash-Mount Remote to designated location with screws.

Unit is installed.

OPERATION OF GOLIGHT®

- 1. Use the toggle switch on the dash control to turn the light on/off.
- 2. The 4-way joystick on the dash control rotates your light to the desired location.

BULB REPLACEMENT

The Golight® utilizes a Philips® H-9 bulb, which may be purchased through Golight, Inc. — 308.278.3131 or 800.557.0098.

IMPORTANT SAFETY INFORMATION

- ★ This symbol is to alert you to important operating or servicing instructions that appear in your instructions. Always follow basic safety precautions when using this product to reduce the risk of injury, fire or electric shock.
- ★ This light is for off road and utility use only. It is not designed for road use as a driving light.
- ★ FCC RULE Part. 15.21 Changes or modifications made by the user not expressly approved by Golight, Inc. for compliance could void the user's authority to operate the equipment.

For safe and efficient operation of your Golight®, observe these guidelines:

Using your Golight® in icing conditions could damage the gear motors. (Optional dome available - see accessory sheet.)