

40 GPM (15 LPM) Washulovin Pump Kit

PAR-MAX SERIES

NEW! Jabsco® Washdown Pumps

- New compact 3 chamber design for greater pumping efficiency
- Flow rates to 4.0 GPM (15 LPM)
- Pressures up to 60 PSI (4.1 bar)
- Model 32605 includes Pumpgard[™]
 Intake Strainer, Pressure Nozzle and Port Fittings
- Model 32900 includes PumpgardTM Intake Strainer, Pressure Nozzle, Port Fittings and 25' of hose coil
- Corrosion resistant
- Sealed Motor
- Self priming up to 6 feet (1.8m)
- ISO 8846 MARINE (ignition protection)





Jabsco continues to lead the pump industry with innovation. This 4.0 GPM (15 LPM) washdown pump provides the boater of small to medium vessels with a cost conscious and size maximized higher pressure pump. With a sealed pump head and motor, this new model provides the same ease of installation as all Jabsco water pressure pumps. Included with each pump is a strainer, nozzle, and fittings for most installations.

Specifications Specification Specification Specification Specification Specification Specification Specification Specification Specification					
Model	Volts	GPM (Ipm)	PSI (bar)	Amps @ 10 psi	25' Coiled Hose
32605-0092	12 VDC	4 (15)	60 (4.1)	9	No
32605-0094	24 VDC	4 (15)	60 (4.1)	4.5	No
32900-0092	12 VDC	4 (15)	60 (4.1)	9	Yes
32900-0094	24 VDC	4 (15)	60 (4.1)	4.5	Yes



Jabsco 4.0 GPM Washdown

Pump

32605-0092......12 Volt 32605-0094......24 Volt **Pump with Kit** 32900-0092......12 Volt


32900-0094......24 Volt

Specifications


- Pump Body Glass Filled Polypropylene
- Pump Design Multi-Chamber Diaphragm
- Suction Lift Self-Priming to 10 ft. (3 m)
- Ports 3/4" (19 mm) Hose Barb & GMT
- Motor Permanent Magnet
- Shipping Weight 5 lb (2.1 kg)


Accessories

Snap-In-Port Systems



Dimensional Drawings Inches (mm)





www.jabsco.com

Pumpgard™

Inlet Strainer

Rule®

Dual Port

Pump



Engineered for life

USA Jabsco/Rule Cape Ann Industrial Park Gloucester, MA 01930 Tel: (978) 281-0440 Fax: (978) 283-2619

UK labsco Bingley Road, Hoddesdon Hertfordshire ENII OBU Tel: +44 (0) 1992 450145

Fax: +44 (0) 1992 467132

CANADA Fluid Products Canada 55 Royal Road Guelph, Ontario NIH ITI Tel: (519) 821-1900

Fax: (519) 821-2569

GERMANY Jabsco GmbH Oststrasse 28 22844 Norderstedt

Tel: +49-40-53 53 73-0 Fax: +49-40-53 53 73-11

Installation

Washdown

Pump

Spray Nozzle

Livewell Tank

JAPAN NHK Jabsco Company Ltd. 3-21-10, Shin-Yokohama Kohoku-Ku, Yokohama, 222-0033 Tel: +81-045-475-8906

Fax: +81-045-477-1162

ITALY Jabsco Marine Italia Via Tommaseo, 6 20059 Vimercate, Milano Tel: +39 039 685 2323 Fax: +39 039 666 307

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.