

The Lightweight Marine-Grade Cellular Sheet

King StarBoard[®] XL is a lightweight, marine-grade, cellular high-density polyethylene sheet that is up to 30% lighter than the original King StarBoard[®]. It is the product of a proprietary process called K-Stran[™], the most advanced manufacturing process for superior flatness and consistency. King StarBoard[®] XL has a matte finish on both sides of the sheet. It is environmentally stabilized to withstand the harshest outdoor conditions. King StarBoard[®] XL will not rust, delaminate or rot when exposed to UV, humidity or water. It is ideal for a variety of marine applications from boat components to equipment mounts, and looks good enough to use in high-visibility applications where structural strength and a finished edge are not important. For maximum versatility, standard colors are made to coordinate with the original King StarBoard[®]. The polymer sheet never needs painting or refinishing, works like wood, and is easy to fabricate with common woodworking tools and techniques.

King StarBoard[®] XL is upgradable to King MicroShield[®] with an advanced antimicrobial technology for protecting the product surface against stain and odor causing bacteria, algae and fungi.*

For more information about King MicroShield[®], please visit www.kingplastic.com

Marine Products





Applications

- Cockpit Covers
- Deck Components
 and Equipment Mounts
- Doorstops and Thresholds
- Electronic Mounts
- Ladder Steps
- Recess Hatches and Bait Well Covers
- Tackle Centers

Specifications

Standard Colors

Standard Sheet Size

in: 60" x 96"mm: 1524 mm x 2438 mm

Standard Gauges

in:	1/4″		3/8"	1/2″	3/4″
mm:	6.4 mm	I	9.53 mm	12.7 mm	19 mm

Approximate Weight

lbs:	40 lbs	61.5 lbs	80 lbs	120 lbs
kg:	18.14 kg	27.89 kg	36.28 kg	54.43 kg

Tolerance information: Gauges 1/4'' up to $3/4'' \pm 5\%$ Length and width plus only at room temperature

Custom sheet sizes, gauges, and colors available

Standard Colors							
Black	Charcoal Gray	Dolphin Gray	Light Gray				
Sanshade	Seafoam	White/White					

Note: Color accuracy can vary considerably on computer monitors and printers. Please consult your distributor for a product sample before making critical color choices. Disclaimer: King MicroShield® may affect color.

*For bacteriostatic, fungistatic, & algistatic properties. This product is exempt from registration under 40 CFR 152.25(a). King MicroShield® effectiveness verified by ISO and ASTM standards. This product does not protect users or others from disease-causing bacteria. Always clean this product thoroughly after use.

Properties	Units	ASTM	Nominal Values
Density	g/cm³	D792	0.77
Tensile Strength @ Yield	psi	D638	>3,300
Tensile Modulus	psi	D638	165,000
Elongation @ Yield	%	D638	9.6
Flexural Modulus	psi	D790	130,000
Flexural Stress @ 5% Strain	psi	D790	2,990
Compressive Properties 10% Strain	psi	D695	2,910
Durometer	Shore D	D2240	64.9
Izod Impact Resistance	ft.lbs./in. ²	D256	1.4
Heat Deflection Temp. 66 psi	°C (°F)	D648	87°C (188°F)
Screw Holding Strength	lbs	D1761	325

All values are determined on specimens prepared according to ASTM. Nominal values should not be interpreted as specifications. King StarBoard[®] XL is made entirely from FDA and USDA approved material.



1100 N. Toledo Blade Blvd. | North Port, FL 34288 USA P: 941.493.5502 | F: 941.497.3274 | www.kingplastic.com

