



# New Viking Universal

## Viking Universal

Heavy duty, self-priming, hand-powered bilge pump for nearly any type of installation.

Viking Universal's mounting bracket allows for vertical or horizontal surface mounting. With the optional Through Deck kit the pump can be installed behind bulkheads or below the deck. To minimize required space the Viking Universal excels at adaption. The simple switching of the valves together with the connections allows you to choose flow direction. The included KlickTite™ straight and 90° hose connections can be used in combination. The hose connections and even the pump housing can be easily rotated for optimal positioning.

While designed as a powerful bilge pump, the Viking Universal's large Ø38 mm (1 1/2") valves enable the pump to also be used for pumping toilet waste.

Fasteners are included for stowing the handle and the safety clasp ensures that the handle cannot be lost while not in use or during an emergency situation. Viking Universal meets ISO 15083, "Bilge pumping systems".

At 45 strokes/min and a 1 m (3.28') head (10 kPa (1.45 psi) pressure) the Viking Universal has a flow of 60 l/min - 16 GPM

Body and cover	Polypropylene plastic reinforced with 30% fiberglass
Diaphragm and valves	Nitrile rubber
Wetted parts	PP30GF, PA66 GF30, POM, stainless steel, nitrile rubber
Maximum suction	3 meters (10')
Maximum head	4 meters (13')
Combined suction/ head	7 meters (23')
Connection	KlickTite™ connectors 38 mm (1 1/2") hose. Both straight and 90° bends are included
Max. liquid temp	+60°C (140°F)
Weight	1,5 kg (3.3 lbs)



Order No.	Description
10-13530-01	VIKING UNIVERSAL WITH CONNECTION DIAMETER 38 MM (1 1/2")
09-36250	VIKING UNIVERSAL THRUDECK KIT

Order No.	Description	Connection
09-47493	CONNECTION, 90° IN/OUT	Ø38
09-47495	CONNECTION, 90° IN/OUT	Ø25
09-47543	CONNECTION, STRAIGHT IN/OUT	Ø38
09-47544	CONNECTION, STRAIGHT IN/OUT	Ø25