




UC94-OBF

FRONT

MOUNT

CYLINDER



SPLASHWELL DIMENSION REQUIREMENTS

Engine No.	A	B	C
1	540 mm - 21.25"	152 mm - 5.98"	152 mm - 5.98"
2	1110 mm - 43.70"	152 mm - 5.98"	152 mm - 5.98"

For twin engine applications, the minimum distance between the two engine centers is 21.6" (550 mm)

UC94-OBF

CYLINDER

APPLICATIONS

WARNING

The UC94-OBF front mount cylinder is recommended for use with outboard engines 150 hp total and less and where the boat speed does not exceed 55 mph (48 knots)

Not intended for use in racing applications

ENGINE	POWER	YEAR	CYLINDER	P. No.
Mercury® Mariner®	50-75-90 2S	1990-2008	UC94-OBF/1	42918 X
	115-125-150 EFI 2S	1990-2007	UC94-OBF/1	42918 X
	75-90-115 OPTIMAX	2004-to date	UC94-OBF/3	42968 N
	135-150 OPTIMAX	1999-to date	UC94-OBF/1	42918 X
	40-50-60 EFI 4S	2004-to date	UC94-OBF/1	42918 X
	75-80-90 EFI 4S	2000-to date	UC94-OBF/1	42918 X
Evinrude®	100-115 EFI 4S	2007-to date	UC94-OBF/1	42918 X
	E40-E50-E55-E60 2S	2004-to date	UC94-OBF/1	42918 X
	E75-E90 2S	2004-to date	UC94-OBF/1	42918 X
	E115-E130-E135 2S V4	1995-to date	UC94-OBF/1	42918 X
Yamaha®	E150 2S V6	1995-to date	UC94-OBF/1	42918 X
	60-70 2S	1984-2008	UC94-OBF/1	42918 X
	75C-90 2S	1998-2008	UC94-OBF/1	42918 X
	115C-130B 2S	1990-2008	UC94-OBF/1	42918 X
	150F	1996-2007	UC94-OBF/1	42918 X
	150 HPDI VMAX 2S	2000-2008	UC94-OBF/1	42918 X
	F60-F75-F80 EFI 4S	1999-2007	UC94-OBF/1	42918 X
	F90-F100-F115-F150 EFI 4S	1999-2007	UC94-OBF/1	42918 X
	F80-F100 4S	2000-to date	UC94-OBF/1	42918 X
	F115-F150 4S	2004-to date	UC94-OBF/1	42918 X
Honda®	BF75-BF90 4S	1995-to date	UC94-OBF/1	42918 X
	BF80-100-115DK-130A 4S	1998-to date	UC94-OBF/1	42918 X
	BF115A-135-BF150 4S	2005-to date	UC94-OBF/1	42918 X
	BF90-BF150 V-TEC 4S	2008-to date	UC94-OBF/1	42918 X
Suzuki®	DF70-80-90 4S	1998-to date	UC94-OBF/1	42918 X
	DF100-115-140 4S	1998-to date	UC94-OBF/1	42918 X
	DF150 4S	2006-to date	UC94-OBF/1	42918 X
Tohatsu® Nissan®	50-60-70-90 2S	2004-to date	UC94-OBF/1	42918 X
	115-120-140 2S	2004-to date	UC94-OBF/1	42918 X
	40-50TLDI 4S	2004-to date	UC94-OBF/1	42918 X
	70-90-115 TLDI 4S	2004-to date	UC94-OBF/1	42918 X
Selva®	50 MADEIRA/ BULL SHARK-60 GREY SHARK/ST.TROPEZ	1995-2008	UC94-OBF/1	42918 X
	70 MAKO SHARK 2S		UC94-OBF/1	42918 X
	80 PORTOFINO/TIGERSHARK 2S		UC94-OBF/1	42918 X
	150 WHITE SHARK 2S	2001-2007	UC94-OBF/1	42918 X
	50-60 DORADO EFI 4S		UC94-OBF/1	42918 X
Johnson®	100EFI MARLIN -115 EFI NARWHAL-150EFI KILLER WHALE 4T	2000-to date	UC94-OBF/1	42918 X
	BJ60-70 4S	2001-2007	UC94-OBF/1	42918 X
	BJ90-115-140 4S	2001-2007	UC94-OBF/1	42918 X
	J90-115 V4 2S	1995-2007	UC94-OBF/1	42918 X

*NOTE:

Suzuki® engines built from 1998 to 2008 installing UC94-OBF/1 cylinder require optional KIT SU - 41954W.